

## NEW MACHINES

**Available from Stock** 



Ask for our best prices!

2 pcs. MATEC 30HV in stock with Control Unit **HEIDENHAIN TNC640** available from May 2024

3 pcs. MATEC 30HV in stock with Control Unit HEIDENHAIN TNC7

available from June 2024

MATEC 30HV with Control Unit SINUMERIK ONE

1 pce. in stock

available from October 2024

 $X = 3,000 \text{ mm} \mid Y = 825 \text{ mm} \mid Z = 1,100 \text{ mm} \text{ (horizontal)} \mid 975 \text{ mm} \text{ (vertical)}$ 

## Basic equipment:

- 1-Axis NC swivel head, swivel radius 300 mm, swivel angle +/- 105°
- Motor spindle 15,000 1/min, 30 kW, 191 Nm
- Tool holder HSK A63
- 48 tool places tool Ø max. 135 mm, tool length max. 460 mm, tool weight max. 10 kg
- NC rotary table with face plate Ø 800 mm, integrated into the machine table, rotation speed • 3D radio touch probe

- max. 25 1/min., with worm drive
- Rapid traverse 30 m/min in all axes
- Working area, fully enclosed, with roof, ergonomic machine front in curved design for optimal accessibility of the machine interior
- Internal coolant supply 20 bar / tank capacity 900 l

## Options - if the production status of the machine allows:

- Provision for additional tool magazine
- Additional tool magazine with 220 places
- Additional control panel
- Mechanical mist collector CMC 1500 J-SP
- Partition wall for double work station system for Y-axis up to 800 mm
- Position of partition wall = 200 mm

- Tool breaking control and measuring of tool length
- Tactile tool breaking control
- RTS table probe for measuring, checking and tool breakage control of cutting tools in the machine
- Collision monitoring UTTec